





Issuance date: 25.08.2023 Validity date: 25.08.2028

Steel structures



Owner of the EPD:

EXBUD Konstrukcje Sp. z o.o. Address: Peryferyjna 23 25-562 Kielce, Poland Tel.: +48 41 335 30 40 Website: http://exbud.pl/

Contact: biuro@exbudkonstrukcje.pl

EPD Program Operator:

Instytut Techniki Budowlanej (ITB)
Address: Filtrowa 1,
00-611 Warsaw, Poland
Website: www.itb.pl
Contact: Michał Piasecki
m.piasecki@itb.pl
energia@itb.pl

ITB is the verified member of The European Platform for EPD program operators and LCA practitioner www.eco-platform.org

Basic information

This declaration is the Type III Environmental Product Declaration (EPD) based on EN 15804+A2 and verified according to ISO 14025 by an external auditor. It contains the information on the impacts of the declared construction materials on the environment and their aspects verified by the independent body according to ISO 14025. Basically, comparison or evaluation of EPD data is possible only if all the compared data were created according to EN 15804+A2.

Life cycle analysis (LCA): A1-A3, A4-A5 and D modules in accordance with EN 15804

(Cradle-to-Gate with options)

The year of preparing the EPD: 2023 Product standard: PN EN 1090-2

Service Life: 100 years

PCR: ITB-PCR A

Declared unit: 1 ton

Reasons for performing LCA: B2B

Representativeness: Poland, European, 2022

MANUFACTURER

EXBUD Konstrukcje company, is located in Peryferyjna Street in Kielce (Poland) and in Köln (Germany) in the field crossborder business activities in Germany. The company is a manufacturer of steel and steel structures elements specialized in the production and processing of steel components and the assembly of structures based on steel solutions, including steel devices and machines. Steel structures produced are applied to civil and industry construction industry infrastructure. The annual manufacturing capacity is 12 000 tonnes of steel



structures depending on types of projects being made. At EXBUD Konstrukcje Sp. z o.o., steel structures are manufactured in accordance with the individual workshop design provided by the client, so the products are unique, adapted to the architectural requirements and installation conditions imposed by the client. Dimensions, type of applied corrosion protection and color of finished elements are different for different projects, and the product is often treated as a one-off. A common feature of the products manufactured by the EXBUD plat is the material from which they are made, i.e. steel, and the standard according to which they are made - PN-EN 1090-2. Steel construction is used to the following objects: production and processing plants, halls, warehouses, logistics and shopping centers, bridges, viaducts, footbridges, public utility facilities, sports, infrastructure and hydro-engineering facilities, facilities for aviation.

PRODUCTS DESCRIPTION

The steel products covered by this EPD have a number of different applications in construction sector. The actual technical documents related to the products are available on website. Set of products covered by this EPD is shown in Table 1.

Table 1. Construction steel products offered by EXBUD konstrukcje Sp. z o.o.

Product types	Grade	Standard
Bars, angles, T-bars	S235/S355	EN 1090-2
Steel columns	S235/S355	EN 1090-2
Construction sections	S235/S355	EN 1090-2

Selected products (Table 1) are commonly used as: prefabricated elements, construction objects such steel structures, buildings/halls skeletons, pressure equipment, machines and mining supports. These products are manufactured in a variety of grades and specifications to comply with national and international quality certifications as well as to meet stringent customer specifications.

LIFE CYCLE ASSESSMENT (LCA) – general rules applied

Unit

The declared unit is 1 ton of product.

System boundary

The life cycle analysis of the declared products covers "Product Stage" A1-A3, A4, C2-C4+D modules in accordance with EN 15804 and ITB PCR A (cradle to gate with options). Energy and water consumption, emissions as well as information on generated wastes were inventoried and were included in the calculation. It can be assumed that the total sum of omitted processes does not exceed 5% of all impact categories. In accordance with EN 15804+A2, machines and facilities (capital goods) required for the production as well as transportation of employees were not included in LCA.

Allocation

The allocation rules used for this EPD are based on general ITB's document PCR A. Production of the covered steel products is a line process (as presented in Figure 1) conducted in the manufacturing plant located in Kielce (Poland). Input and output data from the production is inventoried and allocated to the production on the mass basis. The declaration covers a wide range of steel products. Their production resources and processing stages are basicly similar, so it is possible to average the production by product weight.

System limits

Minimum 99.0% input materials and 100% energy consumption (electricity, gas, LPG, other) were inventoried in a processing plant and were included in the calculation. In the assessment, all significant parameters from gathered production data are considered, i.e. all material used per formulation, utilized thermal energy, and electric power consumption, direct production waste and available emission measurements. Tires consumption for transport was not considered. Substances with a percentage share of less than 0.1% of total mass were excluded from the calculations. The packaging products (wooden pallets) are included.

Modules A1 and A2: Raw materials supply and transport

The modules A1 and A2 represent the extraction and processing of raw materials (mainly steel elements) and transport to the production site. The steel sheets are semi-products commonly used to produce prefabricated elements, skeleton frames, steel structures. Steel used come from a specific suppliers producing steel with EAF technology and BOF. For A2 module (transport) European averages for fuel data are applied.

Module A3: Production

The product specific manufacturing process line is presented in Figure 1, an input steel/semi-product is processed to a dedicated shape. Electricity are consumed in the process. The products are galvanized using two hot-dip and immersion methods, and painted. In the production process, technical gases and materials for welding elements are used. The production process is depicted schematically as can be seen below.




Figure 2 Manufacturing process scheme (A3)

Module A4: transport to consumer

Vehicle transport at distance 700 km is considered (emission standrad: Euro 5) with 100% load capacity.

Modules C and D: End-of-life (EOL)

Due to the fact that the declaration covers a wide range of steel products for various purposes and usage scenarios, it is not possible to directly specify the de-construction technology and the amount of energy for disassembly in C1 module (so this module is very generic based on literature). In the adapted end-of-life scenario, the de-constructed steel products are transported to a steel mill distant by 100 km on > 16t lorry EURO 5 where are used as steel scrap to produce a new steel. The recycling potential of C3 module is 98% and it is assumed that only 2% of the products will end up in a landfill – C4 module (Table 2). Module D presents credits resulting from the recycling of the steel scrap (used for steel production), calculated in accordance with the approach developed by World Steel Association.

Table 2. End-of-life scenario for the steel products

Material	Material recovery	Recycling	Landfilling
Steel scrap	100%	98%	2%

Electricity at end-of-life (module C) has been modelled using an average Polish electricity mix as the location where the product reaches end-of-life is unknown.

Data collection period

The data for manufacture of the declared products refer to period between 01.01.2022 – 31.12.2022 (1 year). The life cycle assessments were prepared for Poland and Europe as reference area.

Data quality

The data selected for LCA originate from ITB-LCI questionnaires completed by EXBUD Konstrukcje Sp. z o.o. and verified during data audit. No data collected is older than five years and no generic datasets used are older than ten years. The representativeness, completeness, reliability, and consistency is judged as good. The background data for the processes come from the following resources database Ecoinvent v.3.9.1 (steel, welding, paints, solvents, foil, paper and carton, EUR-flat pallet, structural timber). Specific (LCI) data quality analysis was a part of the input data verification. Where no background data was available, data gaps were complemented by manufacturer information and literature research.

Assumptions and estimates

The impacts of the representative products were aggregated using weighted average.

Calculation rules

LCA was performed using ITB-LCA tool developed in accordance with EN15804+A2. Emission of greenhouse gases was calculated using the IPCC 2013 GWP method with a 100-year horizon. Emission of acidifying substances, Emission of substances to water contributing to oxygen depletion, Emission of gases that contribute to the creation of ground-level ozone, Abiotic depletion, and ozone depletion emissions where all calculated with the CML-IA baseline method

Additional information

Polish electricity (Eocinvent v 3.9.1 supplemented by actual national Kobize data) emission factor used is 0.702 kg CO₂/kWh. As a general rule, no particular environmental or health protection measures other than those specified by law are necessary.

LIFE CYCLE ASSESSMENT (LCA) - Results

Declared unit

The declaration refers to declared unit (DU) – 1 ton of Steel structures produced in Europe. The following life cycle modules (Table 1) were included in the analysis. The following tables 2-5 show the environmental impacts of the life cycle of selected modules (A1-A5+C1-C4+D).

Table 3. System boundaries for the environmental characteristic of the product.

	Environmental assessment information (MD – Module Declared, MND – Module Not Declared, INA – Indicator Not Assessed)															
Pro	duct sta	age	Constr proc			Use stage						End of life				Benefits and loads beyond the system boundary
Raw material supply	Transport	Manufacturing	Transport to construction site	Construction-installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse-recovery-recycling potential
A1	A2	А3	A4	A 5	В1	B1 B2 B3 B4 B5 B6 B7 C1 C2 C3 (C4	D			
MD	MD	MD	MD	MD	MND	MND	MND	MND	MND	MND	MND	MD	MD	MD	MD	MD

Table 41 Life cycle assessment (LCA) results for specific product – environmental impacts (DU: 1 ton)

Indicator	Unit	A1	A2	А3	A1-A3	A4	A5	C1	C2	C3	C4	D
Global Warming Potential	eq. kg CO ₂	1.12E+03	1.33E+02	3.70E+02	1.62E+03	4.25E+01	6.98E+01	7.02E+00	1.67E+01	1.64E+01	1.06E-01	-6.16E+02
Greenhouse potential - fossil	eq. kg CO ₂	1.12E+03 1.13E+03	1.33E+02 1.33E+02	3.70E+02 3.58E+02	1.62E+03	4.25E+01 4.25E+01	6.85E+01	0.00E+00	1.66E+01	1.64E+01 1.63E+01	1.05E-01	-6.16E+02 -6.08E+02
Greenhouse potential - biogenic	eq. kg CO ₂	-1.90E+01	4.55E-01	1.21E+01	-6.48E+00	3.98E-01	2.00E+00	0.00E+00	5.68E-02	5.57E-02	2.68E-04	-1.24E+01
Global warming potential - land use and land use change	eq. kg CO ₂	6.88E-01	5.22E-02	5.61E-01	1.30E+00	4.57E-02	2.40E-02	0.00E+00	6.52E-03	6.39E-03	9.94E-05	-4.23E-01
Stratospheric ozone depletion potential	eq. kg CFC 11	5.49E-05	3.08E-05	3.45E-05	1.20E-04	2.69E-05	1.40E-06	0.00E+00	3.85E-06	3.77E-06	4.26E-08	2.00E-05
Soil and water acidification potential	eq. mol H+	4.42E+00	5.40E-01	2.40E+01	2.90E+01	4.72E-01	7.60E-01	5.34E-02	6.75E-02	6.61E-02	9.90E-04	-4.99E+00
Eutrophication potential - freshwater	eq. kg P	5.94E-01	8.94E-03	4.00E-01	1.00E+00	7.82E-03	1.30E-01	0.00E+00	1.12E-03	1.10E-03	9.81E-06	-6.32E-01
Eutrophication potential - seawater	eq. kg N	1.02E+00	1.63E-01	1.23E+00	2.40E+00	1.43E-01	1.10E-01	0.00E+00	2.04E-02	2.00E-02	3.45E-04	-6.01E-01
Eutrophication potential - terrestrial	eq. mol N	1.06E+01	1.78E+00	9.91E+01	1.12E+02	1.56E+00	9.30E-01	0.00E+00	2.22E-01	2.18E-01	3.77E-03	-4.18E+00
Potential for photochemical ozone synthesis	eq. kg NMVOC	4.84E+00	5.44E-01	3.26E+00	8.65E+00	4.76E-01	2.60E-01	0.00E+00	6.80E-02	6.67E-02	1.10E-03	-2.92E-01
Potential for depletion of abiotic resources - non-fossil resources	eq. kg Sb	3.35E-03	4.71E-04	7.28E-02	7.67E-02	4.12E-04	3.34E-04	1.78E-07	5.89E-05	5.77E-05	2.42E-07	1.32E-02
Abiotic depletion potential - fossil fuels	MJ	1.25E+04	1.97E+03	5.87E+03	2.03E+04	1.73E+03	1.16E+03	0.00E+00	2.47E+02	2.42E+02	2.89E+00	-7.70E+03
Water deprivation potential	eq. m ³	3.98E+02	9.13E+00	2.65E+02	6.72E+02	7.99E+00	2.40E+01	0.00E+00	1.14E+00	1.12E+00	9.16E-03	-5.25E+01

Table 5 Life cycle assessment (LCA) results for specific product – additional impacts indicators (DU: 1 ton)

Indicator	Unit	A1-A3	A4-A5	C1-C4	D
Particulate matter	disease INA incidence		INA	INA	INA
Potential human exposure efficiency relative to U235	eg. kBq U235	INA	INA	INA	INA
Potential comparative toxic unit for ecosystems	CTUe	INA	INA	INA	INA
Potential comparative toxic unit for humans (cancer effects)	CTUh	INA	INA	INA	INA
Potential comparative toxic unit for humans (non-cancer effects)	CTUh	INA	INA	INA	INA
Potential soil quality index	dimensionless	INA	INA	INA	INA

Table 6 Life cycle assessment (LCA) results for specific product - the resource use (DU: 1 ton)

Table o Elle by old addoddinent (Edi)	/				(= = : : ::::)					ı		
Indicator	Unit	A1	A2	А3	A1-A3	A4	A5	C1	C2	С3	C4	D
Consumption of renewable primary energy - excluding renewable primary energy sources used as raw materials	MJ	2.96E+02	2.83E+01	5.07E+02	8.31E+02	2.48E+01	8.60E+01	0.00E+00	3.54E+00	3.47E+00	0.00E+00	-7.32E+02
Consumption of renewable primary energy resources used as raw materials	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total consumption of renewable primary energy resources	MJ	2.96E+02	2.83E+01	5.07E+02	8.31E+02	2.48E+01	8.60E+01	1.53E-07	3.54E+00	3.47E+00	2.51E-02	-7.32E+02
Consumption of non-renewable primary energy - excluding renewable primary energy sources used as raw materials	MJ	1.27E+04	1.97E+03	6.18E+03	2.08E+04	1.73E+03	1.16E+03	0.00E+00	2.47E+02	2.42E+02	0.00E+00	-8.84E+03
Consumption of non-renewable primary energy resources used as raw materials	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total consumption of non-renewable primary energy resources	MJ	1.27E+04	1.97E+03	6.18E+03	2.08E+04	1.73E+03	1.16E+03	0.00E+00	2.47E+02	2.42E+02	2.89E+00	-8.84E+03
Consumption of secondary materials	kg	1.17E+02	6.62E-01	2.27E-01	1.18E+02	5.79E-01	1.06E-01	0.00E+00	8.27E-02	8.11E-02	6.07E-04	6.36E+02
Consumption of renew. secondary fuels	MJ	2.88E-02	7.29E-03	1.08E-03	3.72E-02	6.38E-03	5.91E-04	9.06E-13	9.11E-04	8.93E-04	1.59E-05	-1.29E+03
Consumption of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	1.50E+00	1.50E+00	0.00E+00	9.39E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-2.35E-01
Net consumption of freshwater	m ³	6.06E+00	2.48E-01	6.22E+00	1.25E+01	2.17E-01	3.15E-01	0.00E+00	3.10E-02	3.04E-02	3.16E-03	5.90E-02

Table 7 Life cycle assessment (LCA) results for specific product – waste categories (DU: 1 ton)

Table 1 Ene by de addedernent (Eer)				io catogorico	/							
Indicator	Unit	A 1	A2	А3	A1-A3	A4	A5	C1	C2	C3	C4	D
Hazardous waste	kg	8.32E-02	2.21E+00	6.75E+00	9.04E+00	1.94E+00	1.20E-02	0.00E+00	2.77E-01	2.71E-01	3.07E-03	-1.03E+01
Non-hazardous waste	kg	3.59E+02	3.93E+01	3.16E+01	4.30E+02	3.44E+01	6.24E-01	0.00E+00	4.92E+00	4.82E+00	4.32E-02	-3.80E+02
Radioactive waste	kg	3.92E-05	1.47E-04	1.65E-05	5.58E-02	1.29E-04	8.70E-04	7.88E-18	1.84E-05	1.81E-05	1.92E-05	-6.49E-03
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	6.67E-02	6.11E-03	9.00E+01	9.01E+01	5.35E-03	1.20E-03	0.00E+00	7.64E-04	7.49E-04	5.78E-06	0.00E+00
Materials for energy recovery	kg	2.15E-04	4.94E-05	1.00E-02	1.03E-02	4.32E-05	1.05E-05	0.00E+00	6.18E-06	6.05E-06	6.85E-08	0.00E+00
Exported Energy	MJ	0.00E+00	0.00E+00	6.20E+00	6.20E+00	0.00E+00	3.46E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Verification

The process of verification of this EPD is in accordance with ISO 14025 and ISO 21930. After verification, this EPD is valid for a 5-year-period. EPD does not have to be recalculated after 5 years, if the underlying data have not changed significantly.

The basis for LCA analysis was EN 15804 and ITB PCR A							
Independent verification corresponding to ISO 14025 (sub clause 8.1.3.)							
x external	internal internal						
External verification of EPD: Halina Prejzner, Ph LCI audit and verification: Michał Chwedaczuk, I LCA, LCI audit and input data verification: Micha	M.Sc. Eng.						

Note 1: The declaration owner has the sole ownership, liability, and responsibility for the for the information provided and contained in EPD. Declarations of construction products may not be comparable if they do not comply with EN 15804+A2. For further information about comparability, see EN 15804+A2 and ISO 14025.

Note 2: Note: ITB is a public Research Organization and Notified Body (EC Reg. no 1488) to the European Commission and to other Member States of the European Union designated for the tasks concerning the assessment of building products' performance. ITB acts as the independent, third-party verification organization (ISO 17025/17065/17029). ITB-EPD program is recognized and registered member of The European Platform - Association of EPD program operators and ITB-EPD declarations are registered and stored in the international ECO-PORTAL.

Normative references

- ITB PCR A General Product Category Rules for Construction Products
- EN 1090-2:2018 Execution of steel structures and aluminium structures Technical requirements for steel structures
- PN-EN 1090-1+A1:2012 Wykonanie konstrukcji stalowych i aluminiowych -- Część 1: Zasady oceny zgodności elementów konstrukcyjnych
- ISO 14025:2006, Environmental labels and declarations Type III environmental declarations Principles and procedures
- ISO 21930:2017 Sustainability in buildings and civil engineering works Core rules for environmental product declarations of construction products and services
- ISO 14044:2006 Environmental management Life cycle assessment Requirements and guidelines
- ISO 15686-1:2011 Buildings and constructed assets Service life planning Part 1: General principles and framework
- ISO 15686-8:2008 Buildings and constructed assets Service life planning Part 8: Reference service life and service-life estimation
- EN 15804:2012+A2:2019 Sustainability of construction works Environmental product declarations –
 Core rules for the product category of construction products
- ISO 14067:2018 Greenhouse gases Carbon footprint of products Requirements and guidelines for quantification
- PN-EN 15942:2012 Sustainability of construction works Environmental product declarations Communication format business-to-business
- ISO 20915:2018 Life cycle inventory calculation methodology for steel products
- KOBiZE Wskaźniki emisyjności CO₂, SO₂, NO_x, CO i pyłu całkowitego dla energii elektrycznej. December 2021
- World Steel Association 2017 Life Cycle inventory methodology report for steel products





Thermal Physics, Acoustics and Environment Department 02-656 Warsaw, Ksawerów 21

CERTIFICATE № 507/2023 of TYPE III ENVIRONMENTAL DECLARATION

Products:

Steel structures

Manufacturer:

EXBUD Konstrukcje Sp. z o.o.

ul. Peryferyjna 23, 25-562 Kielce, Poland

confirms the correctness of the data included in the development of Type III Environmental Declaration and accordance with the requirements of the standard

EN 15804+A2

Sustainability of construction works.

Environmental product declarations.

Core rules for the product category of construction products.

This certificate, issued on 25th August 2023 is valid for 5 years or until amendment of mentioned Environmental Declaration

Head of the Thermal Physic, Acoustics /apd_Environment Department

market miles princered

THE CHNIK! OUDOWL

Deputy Director for Research and Innovation

Kenneted Kenneleid Ship

Warsaw, August 2023